# **ClassBuddy<sup>™</sup> Range**

Cost Effective Charging Solutions

Trolley Dimensions – W590mm H885mm D590mm

Trolley Dimensions – W590mm H1284mm D590mm

32 laptops (2 per bay) with a screen size of up to 15.6" Trolley Dimensions – W748mm H1284mm D590mm

Bay Dimensions – W515mm H66mm D400mm

Bay Dimensions – W335mm H66mm D400mm

Bay Dimensions - W515mm H66mm D400mm

10 laptops with a screen size of up to 17"

16 laptops with a screen size of up to 17"

ClassBuddy 10 - CBYL/CL/010

ClassBuddy 16 - CBYL/CL/016


ClassBuddy 32 - CBYL/CL/032











Trolley Dimensions - W590mm H1284mm D590mm Bay Dimensions – W515mm H66mm D400mm

### ClassBuddy Wall - CBYW/CL/016

ClassBuddy Desk - CBYD/CL/010

16 Chromebooks/tablets with a screen size of up to 14" Cabinet Dimensions – W710mm H677mm D278mm Bay Dimensions – W408mm H35mm D239mm

10 Chromebooks/tablets with a screen size of up to 14"



#### Cabinet Dimensions – W451mm H436mm D405mm Bay Dimensions – W408mm H35mm D239mm



## ClassBuddy Locker 32 - CBYK/CL/032

32 Chromebooks/tablets with a screen size of up to 14" Locker Dimensions – W480mm H13370mm D460mm Bay Dimensions – W280mm H33mm D400mm



ClassBuddy 20 - CBYN/CL/020

20 Chromebooks/tablets (2 per shelf) with a screen size of up to 14" Trolley Dimensions - W590mm H885mm D590mm Bay Dimensions – W515mm H66mm D400mm

- •	
Overview	
Colour	Blue as standard.
	Black, red, yellow or green as special order.
Lifetime Parts & Labour Warranty	1 year on-site. Remainder of warranty return to base.
CE Certified	Fully and independently certified by a notified body.
Security	
Steel Construction	Full steel chassis with piano style hinges.
Secure Locking	Multipoint locking mechanisms.
	Fitted with a keyed cam lock as standard.
Staff Access	Rear or side service doors with separate keys for staff access only.
Charging & Safety	
Charging	All devices are charged simultaneously.
AC Adaptors	Uses the devices own AC Adaptors.
Cable Management	Neat and tidy.
Ultra-Safe Power Management	Three areas of protection for user, equipment and circuits:
	1. Soft-start 2. Surge Protection 3. Residual Voltage Protection
Ventilation	Allows air-flow throughout the unit.
	A temperature controlled fan is added with the Data Transfer option.
Additional Options	
Data Transfer	Update all devices simultaneously (available for Trolleys and Locker).
Locking Options	Keyless locking with PIN code or MiFare lock available.
Timer	20 segment, 7-day digital timer available for factory fitting.
Docking Station	Locks the unit to a wall (available for Trolleys).

### Contact

Michelle Knox - Account Manager E: michelle.knox@lapsafe.com M: +44 (0) 7583 003 226 D: +44 (0) 1787 226 158

