


Mentor™ Range

Intelligent & Secure Charging Trolleys



	Mini Mentor™	Midi Mentor™	Mentor™
Laptops	15	20	30
Tablets	30	40	60
Width	665mm	1240mm	1240mm
Height	1165mm	880mm	1165mm
Depth	605mm	605mm	605mm

Charging Method - The Mentor™ range offers four types of charging; SmartLine, ChargeLine, USB-C & USB

SmartLine Integrated charging cables with LED device charge status indicators

Mini Mentor 15	MINI/SE/015	15 devices with a screen size up to 15.6"
Midi Mentor 20	MIDI/SE/020	20 devices with a screen size up to 15.6"
Mentor 30	MENT/SE/030	30 devices with a screen size up to 15.6"

ChargeLine 3-pin, 13-amp plug sockets (Euro sockets available). Devices charge via their own AC adaptors

Mini Mentor 15	MINI/CE/015	15 devices with a screen size up to 15.6"
Midi Mentor 20	MIDI/CE/020	20 devices with a screen size up to 15.6"
Mentor 30	MENT/CE/030	30 devices with a screen size up to 15.6"

USB-C Universal charging cables supplied per bay, devices charge via the charging cable provided

Mini Mentor 15	MINI/SE/USBC/015	15 devices with a screen size of up to 15.6"
Midi Mentor 20	MIDI/SE/USBC/020	20 devices with a screen size of up to 15.6"
Mentor 30	MENT/SE/USBC/030	30 devices with a screen size of up to 15.6"

USB 2 Universal charging ports supplied per bay, devices charge via their own charging cable

Mini Mentor 30	MINI/SE/030/U	30 devices with a screen size of up to 11"
Midi Mentor 40	MIDI/SE/040/U	40 devices with a screen size of up to 11"
Mentor 60	MENT/SE/060/U	60 devices with a screen size of up to 11"

Alternative bay configurations available per chassis, please check with your Account Manager

Overview	
Future Proof	Upgradeable when the devices change
Mix & Match	With the modular design, devices can be mixed and matched
Lifetime Parts & Labour Warranty	1 year on-site. Remainder - return to base
Colour	Red as standard. Black, Blue, Yellow or Green as special order
Security	
Steel Construction	Fully welded steel chassis, continuous hinges and Anti-jemmy plates
Secure Locking	Multipoint locking mechanisms, fitted with high security locks
Security Hole	Fix the Mentor to a location using the security hole
Charging & Safety	
Power Management	SmartLine protection for in-rush, power surge and residual voltage
Automatic Power Shut Off	ChargeLine provides power shut off to the sockets when the doors are opened
Staff Access	Rear service door with different keys to front and back
Automatic Cooling	Thermostatically controlled fans fitted to keep the trolley cool
Additional Options	
Data Transfer	Update all devices simultaneously
Alarm	Loud motion sensor alarm operated with a keypad
Timer	20 segment, 7-day digital timer available
Docking Station	Locks the unit to a wall / pillar

Contact

Michelle Knox - Account Manager

E: michelle.knox@lapsafe.com

M: +44 (0) 7583 003 226

D: +44 (0) 1787 226 158